


MB720 PCB Terminal Block, Modular



DIMENSIONS/POSITIONS

DIMENSIONS/POSITIONS		MB720-508M	MB720-508M..V
間距	Pitch	5.08mm	5.08mm
位數	Poles	2 ~ 3Poles	2 ~ 3Poles
塑膠本體	Housing Material	PA 66	PA 66
壓線圈	Cage Clamp	Steel, Zinc Plated	Steel, Zinc Plated
端子	Contact	Brass, Tin Plated	Brass, Tin Plated
螺紋	Screw Thread	M2.6, Steel, Zinc Plated	M2.6, Steel, Zinc Plated
電線線徑	Wire Size	14 ~ 22AWG	14 ~ 22AWG
剝線長度	Wire Strip Length	6mm ~ 7mm	6mm ~ 7mm
PCB孔徑	PCB Hole Diameter	1.3mm	1.3mm
最大緊固扭矩	Tightening Torque, Max.	3.5 Lb-in	3.5 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE			
額定電流 I_n	Nominal Current I_n	15A	15A
額定橫截面	Nominal Cross Section	1.5mm ²	1.5mm ²
最大負載電流	Maximum load current	15A	15A
絕緣材料	Insulating Material	PA	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0	V0
額定電壓,CSA/CSAUS Nominal voltage, CSA/CSAUS		300V	300V
額定電流,CSA/CSAUS Nominal current, CSA/CSAUS		15A	15A

