


# OMC120 Pluggable PCB Connector, Plug



MC

## DIMENSIONS/POSITIONS

## OMC120-508

間距	Pitch	5.08mm
位數	Poles	2 ~ 20Poles
塑膠本體	Housing Material	PA 66
壓線圈	Cage Clamp	Brass, Ni Plated
導電夾片	Contact	Phosphor Bronze, Tin Plated
螺紋	Screw Thread	M2.6, Steel, Zinc Plated
電線線徑	Wire Size	12 ~ 24AWG
剝線長度	Wire Strip Length	8mm ~ 9mm
最大緊固扭矩	Tightening Torque, Max.	4.5 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C

## TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE		
額定電流 I <sub>N</sub> Nominal Current I <sub>N</sub>		10A
額定橫截面 Nominal Cross Section		2.5mm <sup>2</sup>
最大負載電流 Maximum load current		10A
絕緣材料 Insulating Material		PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		300V
額定電流,UL/CUL Nominal current, UL/CUL		10A

